

AIRCRAFT MODEL & MFGR. (NO/ENG. MODEL)	ENG. RATINGS (BHP / ALT.)		PROP.	SPEED (M.P.H.)	CLIMB (MIN.)	T.O.&LAND (OVER 50' OBS.)	SPEC. RANGE (MI./H.R./ALT.)	FUEL (U.S. GAL)	BOMBS (L.B.)	WEIGHT (L.B.)	SIZE (FT. & IN.)	WEIGHT (L.B.)	NO. OF CREW	GUNS (NO./CAL./TOT. RDS)	ROCKETS (NO./SIZE/TYP)	BOMBS (NO. & SIZE)	REMARKS	LINE	
	TAKE OFF WAR EMERG. MILITARY NORMAL	MFGR. NO. BLADES DIAMETER TYPE	MAX./H.P./ALT. LANDING (AT DESIGN WT.)	TIME TO ALT. SERV. CEIL. (AT DESIGN WT.)	TAKE OFF LANDING (AT DESIGN WT.)	FERRY NORMAL DESIGN	MÁX. BUILT-IN DESIGN	NONE NORMAL DESIGN	FERRY NORMAL DESIGN	SPAN LENGTH HEIGHT TREAD WING AREA	EMPTY DESIGN GROSS (STRESS)								
P-82E-NA (1) V-1710-143, -145	NO DATA	AERO PRODUCTS (4) 11-0 F. F. CONST. SPD.					EXTERNAL CONFIGURATION SAME AS P-82B: IMPROVED PERFORMANCE: NO OTHER DATA											GR-1 AUTOMATIC PILOT.	1
XP-83 BELL (2) G.E. "J-33"	11500 R.P.M./SL 4000# THRUST/SL 11500 R.P.M./SL 4000# THRUST/SL 1000 R.P.M./SL 3400# THRUST/SL	TWO STAGE CENTRIFUGAL COMPRESSOR		522/ - /15660	11.5/30000	3875	2200/410/40000	1750	NONE	27500	53-0 45-0	14105		6-.50-1800 or 8-.60-1800 & 2-.50-500					2
XP-84 XP-84A REPUBLIC (1) G.E. "J-35-1or-3"	7700 R.P.M./SL 4000# THRUST/SL 7700 R.P.M./SL 4000# THRUST/SL	AXIAL FLOW COMPRESSOR		600/3240# / S L	13.0/35000	4000	2150/423/ -	825	NONE	15200	36-6 36-10	9080		6-.50-1800 (8) 5" HYAR					3
YP-84-RE P-84-RE							PRODUCTION ARTICLE OF YP-84 (NO OTHER DATA AVAILABLE).												4
XP-85 McDONNELL (1) WESTINGHOUSE "24C - 48"	12000 R.P.M./SL 3000# THRUST/SL 12000 R.P.M./SL 3000# THRUST/SL 11000 R.P.M./SL 2050# THRUST/SL	AS ABOVE		664/3000# / S L	-	48900	-	135	NONE	4550	21-0 15-0 6-9	3740		4-.50-1200 NONE NONE			"PARASITE PLANE."	5	
XP-86 NORTH AMERICAN (1) G.E. "J-35-1or-3"	7600 R.P.M./SL 4000# THRUST/SL 7600 R.P.M./SL 4000# THRUST/SL	11 STAGE AXIAL FLOW COMPRESSOR		633/2550# / 18500	15.0/35000	3550	2000/ - / - 1100/400/ - 1300/400/ -	806 420 420	NONE 2000 NONE	16100 15200 13200	40-10 38-4 13-10 9-9 274	9225 13200		8-.50-1602 (8) T-64 ROCKETS			2 x 1000	6	
XP-87 CURTISS (4) WESTINGHOUSE "24C"	12000 R.P.M./SL 3000# THRUST/SL 12000 R.P.M./SL 3000# THRUST/SL 11000 R.P.M./SL 2050# THRUST/SL	AS ABOVE		600/10600# / S L	13.8/35000	6150	2000/450/ - - 1000/450/ -	2400 1380 1380	NONE 2000 NONE	48900 39850 37350	60-0 62-10 - - 600	25830 37350	2 4 2	2-.50-532 4-20mm-1080 PROVISIONS FOR INTERNAL ROCKETS			ALL WEATHER FIGHTER.	7	

Army Aircraft Characteristics Report TSEST-A2, 1 April 1946

A1  
X-85/char